

DUAL OUTPUT MICROPROCESS FREQUENCY ISOLATED TRANSMITTER

MODEL
DTMF

CE



■ FEATURES

- Accuracy 0.03%F.S.
- Input range from 0.01 Hz to 80KHz
- 16 bit DAC isolating analog output
- Dielectric strength 2KVac/lmin. (input/output1/output2/power)
- Wide input range for auxiliary power
- Dimension small and High stability


1. MODEL: DTMF-□ □ □ □

NO	Input Type	NO	Input Type	NO	Input Type	NO	Output 1	NO	Output 1	NO	Output 2	NO	Output 2	NO	Aux. Power
1	Dry contact	5	Magnetic pick-up (AC50mV~1.5V)	7	AC2~60V	A	0~50mV	F	0~1mA	A	0~50mV	F	0~1mA	A	AC/DC 18~60V
2	Pulse(TTL)(5V)			9	SPECIFIED	C	1~5V	H	0~20mA	C	1~5V	H	0~20mA	B	AC/DC 90~260V
3	Pulse(NPN)(12V)	6	Magnetic pick-up (AC500mV~15V)			D	0~10V	I	4~20mA	D	0~10V	I	4~20mA		•Less 4VA for AC/DC input
4	Pulse(PNP)(12V)					E	2~10V	R	SPECIFIED	E	2~10V	R	SPECIFIED		

2. SPCIFICATION

- Measuring accuracy : 0.03% F.S. (23±5°C)
- Count input type : Switch selectable current sourcing(NPN) or current sinking (PNP)
- Count input trigger levels : HI bias (CMOS) ($V_{IH}=7.5V$, $V_{IL}=5.5V$)
LO bias (TTL) ($V_{IH}=3.7V$, $V_{IL}=2.0V$)
- Sampling time : 20 cycles/sec. (>10Hz)
f/2 cycles/sec(<10Hz)
- Analog output resolution : 16 bit DAC
- Response time : <250ms (0~90%)
- Output drive capability : <10mA for voltage mode
<10V for current mode
- Output ripple(p-p) : <0.1% F.S.
- Zero (offset) range : 0~±9999 Digit adjustable(output1)
0~±5%F.S.(output2)
- Span (scale) range : 0~±9999 Digit adjustable(output2)
0~±10%F.S.(output2)
- Sensor power supply : 12VDC±3% (<50mA)
- Temp. coefficient : 50ppm/°C (0~50°C)
- Display : Red high efficiency LEDs high 10.16mm (0.4")
- Isolation : Input/Output1/Output2/Power/Case
- Parameter setting : Touch switches
- Memory mode : Non-volatile E² PROM memory
- Insulation Resistance : >100M ohm with 500V DC
- Dielectric strength : 2KVac/l min. (input/output1/output2/power)
1600Vdc (input/output1/output2)
- Operating condition : 0~60°C (20 to 90% RH non-condensed)
- Storage condition : 0~70°C (20 to 90% RH non-condensed)
- Construction : Socket/plugin type with barrier terminals
- CE EMC Certification : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3. TERMINAL CONNECTION



4. DIMENSION (unit:mm)

