



■ FEATURES

- 5 digit RS-485 display meter
- Readout range form -19999 to 99999 digit
- Modbus RTU mode for RS-485 protocol
- Wide input range for auxiliary power
- Dimension small and High stability

1. MODEL: MMX-RS-□□□

| NO | Display | NO | Case Size | NO | Aux. Power |
|----------------------------|-------------|----|-----------|----------------------------|--------------|
| 1 | One-display | 1 | 24x48mm | A | AC/DC18~60V |
| 2 | Two-display | 2 | 48x96mm | B | AC/DC90~260V |
| • Two-display only 48X96mm | | | | • Less 3VA for AC/DC input | |

2. SPECIFICATION

- Readout range : -19999~99999 digit
- RS-485 baud rate : 19200/9600/4800/2400 selective
- RS-485 address : "01"~"FF"(0~255)
- RS-485 protocol : Modbus RTU mode
- Display : Red high efficiency LEDs high 10.16 mm (0.4")(MMX-RS-11X)
Red high efficiency LEDs high 20.32 mm (0.8")(MMX-RS-12X)
Red high efficiency LEDs high 10.16 mm (0.4")x2(MMX-RS-22X)
- Parameter setting : Touch switches
- Memory mode : Non-volatile E² PROM memory
- Dielectric strength : 2KVac/1 min. (input/power)
- Operating condition : 0~50°C (20 to 90% RH non-condensed)
- Storage condition : 0~70°C (20 to 90% RH non-condensed)
- CE EMC Certification : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3. OUTSIDE DIMENSION AND CONNECTION DIAGRAM

