



**FEATURES**

- 5 digit RS-485 display meter
- Readout range form -19999 to 99999 digit
- Modbus RTU mode for RS-485 protocol
- Wide input range for auxiliary power
- Dimension small and High stability

**1.MODEL:MMX-RS-**

NO	Display	NO	Case Size	NO	Aux. Power
1	One-display	1	24x48mm	A	AC/DC18-60V
2	Two-display	2	48x96mm	B	AC/DC90-260V
Two-display only 48X96mm				Less 3VA for AC/DC input	

**2.SPECIFICATION**

- Readout range : -19999~99999 digit
- RS-485 baud rate : 19200/9600/4800/2400 selective
- RS-485 adress : "01"-"FF"
- RS-485 protocol : Modbus RTU mode
- Display : Red high efficiency LEDs high 10.16 mm (0.4") (MMX-RS-11X)  
Red high efficiency LEDs high 20.32 mm (0.8") (MMX-RS-12X)  
Red high efficiency LEDs high 10.16 mm (0.4")x2 (MMX-RS-22X)
- Parameter setting : Touch switches
- Memory mode : Non-volatile E<sup>2</sup> PROM memory
- Dielectric strength : 2KVac/1 min. (input/power)
- Operating condition : 0-50 (20 to 90% RH non-condensed)
- Storage condition : 0-70 (20 to 90% RH non-condensed)
- CE EMC Certification : EN 55022:1998/A1:2000 Class A  
EN 61000-3-2:2000  
EN 61000-3-3:1995/A1:2001  
EN 55024:1998/A1:2001

**3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM**

